

ALPINE SHALLOW 2IN

A1RC-A46 Round Adjustable Trim



Fixture Type:

Catalog Number:

Project:

Location:

FINISHES



Trim (See next page for housing)

Model	Beam	Color Temp	CRI	Lumens	CBCP	Finishes
A1RC-A46 Round, 0-300 Adjustable Damp Location	S 15°	27 2700K 30 3000K	90 90	690 720	6625 6935	BK Black BKWT Black/White HZWT Haze/White WT White
	N 26°	27 2700K 30 3000K	90 90	1050 1095	3535 3680	
	F 40°	27 2700K 30 3000K	90 90	1045 1090	2085 2170	
A1RC-A46 Round, 0-250 Adjustable Lensed, Wet Location	S 16°	27 2700K 30 3000K	90 90	630 660	5115 5355	LBK Lensed Black LBKWT Lensed Black/White LHZWT Lensed Haze/White LWT Lensed White
	N 28°	27 2700K 30 3000K	90 90	970 1015	3050 3175	
	F 40°	27 2700K 30 3000K	90 90	960 1000	1840 1915	

Example: A1RC-A46N-27WT

DESCRIPTION

Shallow housing that is designed to fit in tight plenum spaces without sacrificing lumen output.

FEATURES

- Designed to fit in tight plenum
- 2" trim aperture, 2" housing height
- Damp Location Trims: 0-30° vertical and 365° horizontal adjustment
- Wet Location Trims: 0-25° vertical and 365° horizontal adjustment
- 8 year product warranty

SPECIFICATIONS

Construction:	Die-cast aluminum trim with die-cast aluminum heat sink
Dimming:	100% - 5% with 0-10V 100% - 5% with Electronic Low Voltage (ELV)/ TRIAC
Input:	120V-277V AC
Power:	15W, power factor 0.9
Mounting:	Retention clips firmly hold trim to housing.
Finish:	Powder coated White, Black/White, Haze/White, Black
Standards:	UL & cUL Damp Listed, UL & cUL Wet Listed (Lensed options only), Title24 JA8 Compliant
Ceiling thickness:	1/2" - 1"

ALPINE SHALLOW 2IN

A1RC-268 Housing



Fixture Type:

Catalog Number:

Project:

Location:

FINISHES



Black

Model

Finish

A1RC-268	<i>New Construction IC-rated, Airtight</i>	Black
-----------------	--	-------

Example: **A1RC-268**

LINE DRAWING

