

ALPINE SHALLOW 2IN

A1RC-A47 Round Adjustable Trimless



Fixture Type:

Catalog Number:

Project:

Location:

FINISHES



Black



Haze



White

Trim (See next page for housing)

Model

Beam

Color Temp

CRI

Lumens

CBCP

Finishes

	A1RC-A47 Round, 0-30° Adjustable Damp Location	S 15°	27 30	2700K 3000K	90 90	690 720	6625 6935	BK Black HZ Haze WT White
		N 26°	927 30	2700K 3000K	90 90	1050 1095	3535 3680	
		F 40°	27 30	2700K 3000K	90 90	1045 1090	2085 2170	
	A1RC-A47 Round, 0-25° Adjustable Lensed, Wet Location	S 16°	27 30	2700K 3000K	90 90	630 660	5115 5355	LBK Lensed Black LHZ Lensed Haze LWT Lensed White
		N 28°	27 30	2700K 3000K	90 90	970 1015	3050 3175	
		F 40°	927 930	2700K 3000K	90 90	960 1000	1840 1915	

Example: A1RC-A47N-27BK

DESCRIPTION

Shallow housing that is designed to fit in tight plenum spaces without sacrificing lumen output.

FEATURES

- Designed to fit in tight plenum
- 2" trim aperture, 2" housing height
- Damp Location Trims: 0-30° vertical and 365° horizontal adjustment
- Wet Location Trims: 0-25° vertical and 365° horizontal adjustment
- 8 year product warranty

SPECIFICATIONS

Construction:	Die-cast aluminum trim with die-cast aluminum heat sink
Dimming:	100% - 5% with 0-10V 100% - 5% with Electronic Low Voltage (ELV)/ TRIAC
Input:	120V-277V AC
Power:	15W, power factor 0.9
Mounting:	Retention clips firmly hold trim to housing.
Finish:	Powder coated White, Black/White, Haze/White, Black, electroplated brushed nickel
Standards:	UL & cUL Damp Listed, UL and cUL Wet Listed (lensed options only), Title 24 JA8 Compliant
Ceiling thickness:	1/2" - 1"

ALPINE SHALLOW 2IN

A1RC-268 Housing



Fixture Type:

Catalog Number:

Project:

Location:

FINISHES



Black

Model		Finish
A1RC-268	New Construction IC-rated, Airtight	Black

Example: A1RC-268

LINE DRAWING

