

ASTRO 3.5" Adjustable Downlight

A1RE-D46-DW, A1RE-D47-DW



Fixture Type:

Catalog Number:

Project:

Location:

FINISHES



White



Haze White



Haze

Model	Power	Beam	Color Temp	Max Lumens	Max CBCP	Finish
A1RE-D46-DW Round Trim Adjustable Downlight	13W	Narrow Flood 34° Flood 60°	3000K-1800K	860 750	2110 665	WT White HZWT Haze White
	16W	Narrow Flood 34° Flood 60°	3000K-1800K	1020 890	2500 785	WT White HZWT Haze White
A1RE-D47-DW Round Trimless Adjustable Downlight	13W	Narrow Flood 34° Flood 60°	3000K-1800K	860 750	2110 665	WT White HZ Haze
	16W	Narrow Flood 34° Flood 60°	3000K-1800K	1020 890	2500 785	WT White HZ Haze

Example: A1RE-D46-DW-WT

DESCRIPTION

The brilliant LED recessed downlight that gradually changes to a warmer color temperature as you dim. Great for new construction projects or remodels.

FEATURES


- 2 beam angle options included - Narrow flood beam pre-installed, interchangeable flood beam film supplied
- Non IC and IC-Rated, Airtight, New Construction, Remodel
- Adjustable LED light engine included with housing: Vertical Adjustment 0-30°, Horizontal Adjustment 360°
- Shallow housing under 4" depth
- 5 year warranty

LINE DRAWING

A1RE-D47-DW
Round Trimless
Adjustable Downlight



A1RE-D46-DW
Round Trim
Adjustable Downlight



SPECIFICATIONS

Construction:	Die-cast aluminum trim and heat sink
Power:	13W/16W
Input:	120V-277V 50/60Hz
Dimming:	100% - 1% TRIAC, ELV 100% - 5%, 0-10V
Light Source:	CRI 95 high output COB LED rated life of 50,000 hours
Mounting:	Retention clips firmly hold trim to housing. Cutout: 4 1/4" New Construction Housing 3 7/8" Remodel Housing
Finish:	Powder coated white, haze.
Ceiling Thickness:	1/2" - 1"
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL & cUL, Wet Location listed, Title 24 JA8-2019 Compliant

aispire.com Phone (800) 568.2005 Fax (800) 526.2585	Headquarters, East Manufacturing Facility 44 Harbor Park Drive Port Washington, NY 11050	South East Manufacturing Facility 1600 Distribution Ct Lithia Springs, GA 30122	Central Manufacturing Facility 1700 South J Elmer Freeway, Ste 100 Cedar Hill, TX 75104	West Manufacturing Facility 1750 S Archibald Ave Ontario, CA 91761
---	--	---	---	--

ASTRO 3.5" Adjustable Downlight
A1RE-D46-DW, A1RE-D47-DW



Model	Model	Power		Color Temp
	A1RE-248M IC-Rated Airtight	13W		
	A1RE-148M Non IC- Rated Airtight	16W	DW	3000K-1800K
	A1RE-346M Non IC- Rated Airtight	16W	DW	3000K-1800K
	A1RE-347M Non IC- Rated Airtight	16W	DW	3000K-1800K

Example: **A1RE-346M-DW**



FEATURES

- Dim to warm technology
- Line voltage direct to the housing with "Intuitive style" dimming that replicates halogen and incandescent warmth
- High lumen density for directional lighting
- Compatible with most single channel drivers and dimmer switches
- Up to 97CRI (typical) at 3000K dimming down to 1800K for residential and hospitality lighting
- Consistent white light <3 SDCM

APPLICATIONS

- Hospitality, hotel, and restaurant lighting
- Bedrooms, bathrooms, theaters, great rooms, and lower levels
- Retail shop lighting
- Public, commercial buildings

CCT CHANGE DIMMING CURVE

