

# ALPINE

## A1RE-P46, A1RE-P47 3.5" Adjustable Pinhole



Fixture Type:

Catalog Number:

Project:

Location:



White

Trim (Order Housing Separately)	Model	Beam	Color Temp	Lumens	CBCP	Finish
	A1RE-P46 Round Trim Adjustable Pinhole	Spot 16°	927 2700K 930 3000K	720 770	5008 5385	WT White
		Narrow Flood 32°	927 2700K 930 3000K	630 675	1425 1532	
		Flood 44°	927 2700K 930 3000K	580 623	824 886	
	A1RE-P47 Round Trimless Adjustable Pinhole	Spot 16°	927 2700K 930 3000K	720 770	5008 5385	WT White
		Narrow Flood 32°	927 2700K 930 3000K	630 675	1425 1532	
		Flood 44°	927 2700K 930 3000K	580 625	824 886	

A1RE-P4\_--

Example: A1RE-P46-WT

### DESCRIPTION

Alpine offers performance features in a simple but versatile package for residential and commercial applications alike. One housing can be used for downlight, adjustable, pinhole, wall wash trims.

### FEATURES

- 3 beam angle options included: For Wall Wash trim optimal optics is light engine with no film installed.
- IC-Rated, Airtight, New Construction
- Adjustable LED light engine included with housing
- Shallow housing under 4" depth
- 5 year warranty

### SPECIFICATIONS

<b>Construction:</b>	Die-cast aluminum trim and heat sink
<b>Power:</b>	13.5W
<b>Input:</b>	120V-277V 50/60Hz
<b>Dimming:</b>	100% - 1% TRIAC, ELV 100% - 5%, 0-10V
<b>Light Source:</b>	High output COB LED rated life of 50,000 hours.
<b>Mounting:</b>	Retention clips firmly hold trim to housing.  Cut Out: 4 1/4" New Construction Housing 3 7/8" Remodel Housing
<b>Finish:</b>	Powder coated white
<b>Ceiling Thickness:</b>	1/2" - 1"
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)
<b>Standards:</b>	UL & cUL, Wet Location listed, Title 24 JA8-2019 Compliant

ALPINE  
A1RE-P46, A1RE-P47 3.5" Adjustable Pinhole



Model	Model	Power	Color Temp
	<b>A1RE-248M</b> IC-Rated Airtight	13.5W	<b>27</b> 2700K <b>30</b> 3000K
	<b>A1RE-346M</b> Non IC Airtight	13.5W	<b>27</b> 2700K <b>30</b> 3000K
	<b>A1RE-347M</b> Non IC Airtight	13.5W	<b>27</b> 2700K <b>30</b> 3000K

Example: **A1RE-248M-27**

FEATURES

- Adjustable LED light engine included with housing: Optimal Vertical Adjustment for Wall Wash is 15° indexed position
- Trim or trimless with die-cast spackle frame included.
- Accepts one optional honeycomb louver or optical lens.

GLARE CONTROL ACCESSORIES sold separately

LENS-16	Honeycomb Louver
---------	------------------

LENS ACCESSORIES sold separately

LENS-16	<b>AMB</b> Amber <b>RED</b> Red <b>FR</b> Frosted <b>SPR</b> Spread <b>BEL</b> Beam Elongating
---------	--