

ALPINE

A1RE-P56, A1RE-P57 3.5" Adjustable Pinhole



Fixture Type:

Catalog Number:

Project:

Location:

FINISHES



White

Trim (Order Housing Separately)	Model	Beam	Color Temp	Lumens	CBCP	Finish
	A1RE-P56 Square Trimless Adjustable Pinhole	Spot 16°	27 2700K 30 3000K	755 810	5004 5380	WT White
		Narrow Flood 32°	27 2700K 30 3000K	705 760	1373 1477	
		Flood 44°	27 2700K 30 3000K	645 695	791 851	
	A1RE-P57 Square Trim Adjustable Pinhole	Spot 16°	27 2700K 30 3000K	755 810	5004 5380	WT White
		Narrow Flood 32°	27 2700K 30 3000K	705 760	1373 1477	
		Flood 44°	27 2700K 30 3000K	645 695	791 851	

A1RE-P5_--

Example: A1RE-P56-WT

DESCRIPTION

ALPINE offers performance features in a simple but versatile package for residential and commercial applications alike. One housing can be used for downlight, adjustable, pinhole, wall wash trims.

FEATURES

- 3 beam angel options included:
- Narrow flood beam film pre-installed, interchangeable flood beam film supplied, remove film for spot beam
- IC-Rated, Airtight, New Construction
- Adjustable LED light engine included with housing:
- Vertical Adjustment 0-30°, Horizontal Adjustment 360°
- Shallow housing under 4" depth
- 5 year warranty

SPECIFICATIONS

Construction:	Die-cast Aluminum trim and heat sink
Power:	13.5W
Input:	120-277V, 50/60Hz
Dimming:	100%-1% ELV, TRIAC 100%-5% 0-10V
Light Source:	High output COB LED
Lens:	Frosted TIR lens
Rated Life:	50000 Hours
Mounting:	Retention clip firmly hold trim to housing Cut Out: 4 1/4" x 4 1/4" New Construction Housing 3 7/8" x 3 7/8" Remodel Housing
Finish:	Powder Coated White
Ceiling Thickness:	1/2" - 1"
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Wet Location Listed, Title 24 JA8-2019 Compliant, IC, Airtight

ALPINE
A1RE-P56, A1RE-P57 3.5" Adjustable Pinhole



Housing (Required) - Order seperately from trims

Housing (Required) - Order seperately from trims	Model	Power	Color Temp
	A1RE-258M IC-Rated Airtight	13.5W	27 2700K 30 3000K
	A1RE-356M Non IC- Rated Airtight	13.5W	27 2700K 30 3000K
	A1RE-357M Non IC- Rated Airtight	13.5W	27 2700K 30 3000K

A1RE-__ M-__

Example: A1RE-258M-27

FEATURES

- Adjustable LED light engine included with housing: Vertical Adjustment 0-30°, Horizontal Adjustment 365°
- Trim or trimless with die-cast spackle frame included
- Accepts one optional honeycomb louver or optical lens

GLARE CONTROL ACCESSORIES sold separately

LENS-16	HCL	Honeycomb Louver
----------------	------------	------------------

LENS ACCESSORIES sold separately

LENS-16	AMB	Amber
	RED	Red
	FR	Frosted
	SPR	Spread
	BEL	Beam Elongating