

ALPINE

A1RE-W46, A1RE-W47 3.5" Wall Wash



Fixture Type:

Catalog Number:

Project:

Location:

FINISHES



White



Haze



Haze/White

| | Model | Beam | Color Temp | Lumens | CBCP | Finish |
|--|---|--------------|------------|--------|------|-----------------|
| | A1RE-W46 Round Trim Wall Wash | Asymmetrical | 27 2700K | 590 | N/A | WT White |
| | | | 30 3000K | 635 | | HZWT Haze/White |
| | A1RE-W47 Round Trimless Wall Wash | Asymmetrical | 27 2700K | 590 | N/A | WT White |
| | | | 30 3000K | 635 | | HZ Haze |

Example: A1RE-W46-WT

DESCRIPTION

Alpine offers performance features in a simple but versatile package for residential and commercial applications alike. One housing can be used for downlight, adjustable, pinhole, wall wash trims.

FEATURES

- 3 beam angle options included: For Wall Wash trim optimal optics is light engine with no film installed.
- IC-Rated, Airtight, New Construction
- Adjustable LED light engine included with housing
- Shallow housing under 4" depth
- 5 year warranty

SPECIFICATIONS

| | |
|---------------------------|---|
| Construction: | Die-cast aluminum trim and heat sink |
| Power: | 13.5W |
| Input: | 120V-277V 50/60Hz |
| Dimming: | 100% - 1% TRIAC, ELV 100% - 5%, 0-10V |
| Light Source: | High output COB LED rated life of 50,000 hours. |
| Mounting: | Retention clips firmly hold trim to housing. Cutout Cut Out: 4 1/4" New Construction Housing 3 7/8" Remodel Housing |
| Finish: | Powder coated white, enamel-coated haze. |
| Ceiling Thickness: | 1/2" - 1" |
| Operating Temp: | -4°F to 104°F (-20°C to 40°C) |
| Standards: | UL & cUL, Wet Location listed, Title 24 JA8-2019 Compliant |

ALPINE

A1RE-W46, A1RE-W47 3.5" Wall Wash



| Model | | Model | Power | Color Temp |
|-------------------------|--|--|-------|--|
| | | A1RE-248M IC-Rated Airtight | 13.5W | 27 2700K 30 3000K |
| <p>Remodel Trim</p> | | A1RE-346M Non IC Airtight | 13.5W | 27 2700K 30 3000K |
| <p>Remodel Trimless</p> | | A1RE-347M Non IC Airtight | 13.5W | 27 2700K 30 3000K |

Example: **A1RE-248M-27**

FEATURES

- Adjustable LED light engine included with housing: Optimal Vertical Adjustment for Wall Wash is 15° indexed position
- Trim or trimless with die-cast spackle frame included.
- Accepts one optional honeycomb louver or optical lens.

GLARE CONTROL ACCESSORIES sold separately

| | |
|---------|------------------|
| LENS-16 | Honeycomb Louver |
|---------|------------------|

LENS ACCESSORIES sold separately

| | |
|---------|--|
| LENS-16 | AMB Amber RED Red FR Frosted SPR Spread BEL Beam Elongating |
|---------|--|