



Alpine Adjusto Multiples

A1RG Trimmed



DESCRIPTION

Retractable, adjustable spot lights

FEATURES

- Continuously adjustable beam angle between 15° and 45°
- 365° horizontal rotation and 180° vertical aiming
- Independently adjustable and retractable heads
- Accommodates one lens and glare control accessory
- 5 year WAC Lighting warranty

Fixture Type:





Catalog Number:

Project:

Location:

SPECIFICATIONS

Construction:	Die-cast Aluminum with rotatable front face. Steel housing and trim.
Power:	Reference table below
Input:	Universal 120-277 VAC, 50/60Hz
Dimming:	Electronic low voltage (ELV), TRIAC, 0-10V
Light Source:	High output LED
Rated Life:	50,000 Hours
Mounting:	Accommodates 1/2" - 1" ceiling thickness
Finish:	Electrostatically Powder Coated Black and White
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL & cETL Damp location listed Title 24 JA8-2019 Compliant, Airtight

Model	Power	Rating	Heads	Color Temp	CRI	Beam	Lumens *Ref. Output	CBCP *Ref. Output	Finish (Trim/Interior)
A1RG	256 10W 156 14W	IC Non IC		1D	27 2700K 90 30 3000K 90	15° 45°	745 1130	3460 1870	WTWT White/White WTBK White/Black BK BK Black/Black
A1RG	256 20W 156 28W	IC Non IC		2D	27 2700K 90 30 3000K 90	15° 45°	745 x2 1130 x2	3460 x2 1870 x2	WTWT White/White WTBK White/Black BK BK Black/Black
A1RG	256 30W 156 42W	IC Non IC		3D	27 2700K 90 30 3000K 90	15° 45°	745 x3 1130 x3	3460 x3 1870 x3	WTWT White/White WTBK White/Black BK BK Black/Black
A1RG	256 40W 156 56W	IC Non IC		4D	27 2700K 90 30 3000K 90	15° 45°	745 x4 1130 x4	3460 x4 1870 x4	WTWT White/White WTBK White/Black BK BK Black/Black

Example: **A1RG-1561D-30WTWT**

*Reference output is 30(CRI 90 3000k) at 1(14W). Reference photometric performance on next page for other combinations.

aispire.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

Alpine Adjusto Multiples

A1RG Trimmed

PHOTOMETRIC PERFORMANCE (PER HEAD):

10W

Model	Power	Color Temp	CRI	Beam	Lumens	CBCP
A1RG-2	<i>10W</i>	927 2700K	90	15°	520	2440
				45°	780	1305
		930 3000K	90	15°	555	2585
				45°	835	1400

14W

Model	Power	Color Temp	CRI	Beam	Lumens	CBCP
A1RG-1	<i>14W</i>	927 2700K	90	15°	690	3250
				45°	1050	1735
		930 3000K	90	15°	745	3460
				45°	1130	1870

ACCOMMODATES ONE LENS ACCESSORY AND ONE GLARE CONTROL ACCESSORY

FLAT LENS

Amber	LENS-16-AMB
Blue	LENS-16-BLU
Green	LENS-16-GRN
Red	LENS-16-RED

FLAT LENS

Frosted	LENS-16-FR
Spread	LENS-16-SPR
Beam Elongating	LENS-16-BEL

GLARE CONTROL

Cross louver - Black	LENS-16P-CRL-BK
Cross louver - White	LENS-16P-CRL-WT
Snoot - Black	LENS-16-SNOOT-BK
Snoot - White	LENS-16-SNOOT-WT
Honey Comb Louver	LENS-16-HCL

REPLACEMENT HEADS(INCLUDES: ONE HEAD, LED, AND DRIVER)

Model	Power	
4A1RG-2D-27BK 4A1RG-2D-30BK	<i>10W</i>	<i>IC</i>
4A1RG-2D-27WT 4A1RG-2D-30WT	<i>10W</i>	<i>IC</i>
4A1RG-1D-27BK 4A1RG-1D-30BK	<i>14W</i>	<i>Non IC</i>
4A1RG-1D-27WT 4A1RG-1D-30WT	<i>14W</i>	<i>Non IC</i>

Example: **4A1RG-2D-30WT**