



Alpine Adjusto Multiples

A1RG Trimless



DESCRIPTION

Retractable, adjustable spot lights

FEATURES

- Continuously adjustable beam angle between 15° and 45°
- 365° horizontal rotation and 180° vertical aiming
- Independently adjustable and retractable heads
- Accommodates one lens and glare control accessory
- 5 year WAC Lighting warranty

Fixture Type:





Catalog Number:

Project:

Location:

SPECIFICATIONS

Construction:	Die-cast Aluminum with rotatable front face. Steel housing and trim.
Power:	Reference table below
Input:	Universal 120-277 VAC, 50/60Hz
Dimming:	Electronic low voltage (ELV), TRIAC, 0-10V
Light Source:	High output LED
Rated Life:	50,000 Hours
Mounting:	Accommodates 1/2" - 1" ceiling thickness
Finish:	Electrostatically Powder Coated Black and White
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL & cETL Damp location listed Title 24 JA8-2019 Compliant, Airtight

Model	Power		Rating		Heads	Color Temp		CRI	Beam	Lumens *Ref. Output	CBCP *Ref. Output	Finish (Trim/Interior)
A1RG	257	10W	IC Non IC		1D	27	2700K	90	15°	745	3460	WTWT White/White WTBK White/Black
	157	14W				30	3000K	90	45°	1130	1870	
A1RG	257	20W	IC Non IC		2D	27	2700K	90	15°	745 x2	3460 x2	WTWT White/White WTBK White/Black
	157	28W				30	3000K	90	45°	1130 x2	1870 x2	
A1RG	257	30W	IC Non IC		3D	27	2700K	90	15°	745 x3	3460 x3	WTWT White/White WTBK White/Black
	157	42W				30	3000K	90	45°	1130 x3	1870 x3	
A1RG	257	40W	IC Non IC		4D	27	2700K	90	15°	745 x4	3460 x4	WTWT White/White WTBK White/Black
	157	56W				30	3000K	90	45°	1130 x4	1870 x4	

Example: **A1RG-1571D-30WTWT**

*Reference output is **30**(CRI 90 3000K) at **1**(14W). Reference photometric performance on next page for other combinations.

aispire.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

Alpine Adjusto Multiples

A1RG Trimless

PHOTOMETRIC PERFORMANCE (PER HEAD):

10W

Model	Power	Color Temp	CRI	Beam	Lumens	CBCP	
A1RG-2	10W	927 2700K	90	15°	520	2440	
				45°	780	1305	
		930 3000K	90	15°	555	2585	
				45°	835	1400	

14W

Model	Power	Color Temp	CRI	Beam	Lumens	CBCP	
A1RG-1	14W	927	2700K	90	15°	690	3250
					45°	1050	1735
		930	3000K	90	15°	745	3460
					45°	1130	1870

ACCOMMODATES ONE LENS ACCESSORY AND ONE GLARE CONTROL ACCESSORY

FLAT LENS

Amber	LENS-16-AMB
Blue	LENS-16-BLU
Green	LENS-16-GRN
Red	LENS-16-RED

FLAT LENS

Frosted	LENS-16-FR
Spread	LENS-16-SPR
Beam Elongating	LENS-16-BEL

GLARE CONTROL

Cross louver - Black	LENS-16P-CRL-BK
Cross louver - White	LENS-16P-CRL-WT
Snoot - Black	LENS-16-SNOOT-BK
Snoot - White	LENS-16-SNOOT-WT
Honey Comb Louver	LENS-16-HCL

REPLACEMENT HEADS(INCLUDES: ONE HEAD, LED, AND DRIVER)

Model	Power	
4A1RG-2D-27BK 4A1RG-2D-30BK	<i>10W</i>	<i>IC</i>
4A1RG-2D-27WT 4A1RG-2D-30WT	<i>10W</i>	<i>IC</i>
4A1RG-1D-27BK 4A1RG-1D-30BK	<i>14W</i>	<i>Non IC</i>
4A1RG-1D-27WT 4A1RG-1D-30WT	<i>14W</i>	<i>Non IC</i>

Example: **4A1RG-2D-30WT**