

# A1RS-A47M-C2

## QUARTUS ATMOSPHERE 2" - Round Adjustable Trimless



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### PRODUCT DESCRIPTION

QUARTUS ATMOSPHERE recessed luminaires merge quality and value with the latest tunable white technology to demonstrate the beauty and power of 90 CRI illumination. Ideal for sunrise/sunset scenes, as well as accenting artwork, furniture and architectural decor while creating personalized and meaningful experiences for your clients.

### FEATURES

- Two-piece die-cast construction
- Light engine mounted on trim with springs for easy replacement
- 0-35° vertical tilting and 365° horizontal rotation
- Center beam alignment retained throughout adjustment range
- Field changeable beam angle with reflectors provided
- Accepts one Lens or glare control accessory
- 8 year product warranty

### SPECIFICATIONS

- Construction:** Durable die-cast aluminum construction
- Input:** Universal 120-277V AC 50/60 Hz
- Dimming:** 2-channel DMX512-A RDM:: 100%-0.1%
- Light Source:** 3-step Mac Adam Ellipse Tunable White COB  
Rated life of 50,000 hours at L70
- Mounting:** Heavy gauge retention clips support trim firmly.  
Safety cabling standard.
- Finish:** Electrostatically powder coated White, Black, Dark Bronze. Enamel coated Haze.
- Standards:** ETL & cETL Damp Location Listed, Title 24 JA8 Compliant.

	Model	Beam	*Lumens	*CBCP	Color Temp	CRI	Finishes	Reflector/Trim
	<b>A1RS-A47M</b> Round Trimless	N 30°	980	2165	<b>C2</b> 1800K - 4000K	90	<b>BK</b> <b>DB</b> <b>HZ</b> <b>WT</b>	Black Dark Bronze Haze White
		F 42°	915	1310				
		W 55°	920	1025				

### A1RS-A47M-C2\_\_

Example: **A1RS-A47M-C2WT** (Beam N-30° reflector is pre-installed. Beams F-42° and W-55° reflectors are included.)

\* Lumens and CBCP are reference values for 3000K trim with 2 housing. Use multiplier table below to determine the output for other combinations.

LUMENS AND CBPC MULTIPLIER						
Housing Power Level	Color Temperature					
	1800K	2200K	2700K	3000K	3500K	4000K
<b>1 (14W)</b>	0.59	0.69	0.76	0.80	0.85	0.88
<b>2 (18W)</b>	0.74	0.86	0.95	1.00	1.06	1.10

Please see next page for housing units (required)

aispire.com	<b>Headquarters</b>	<b>Georgia Distribution Center</b>	<b>Texas Distribution Center</b>	<b>California Distribution Center</b>
Phone (800) 526.2588	44 Harbor Park Drive,	1600 Distribution Ct,	1700 S J Elmer Weaver Fwy Suite 100,	1750 S Archibald Ave,
Fax (800) 526.2585	Port Washington, NY 11050	Lithia Springs, GA 30122	Cedar Hill, TX 75104	Ontario, CA 91761

# A1RS-A47M-C2

QUARTUS ATMOSPHERE 2" - Round Adjustable Trimless

*HOUSING (Required)*

		<i>Model</i>	<i>Power</i>
<b>New Construction IC Airtight</b>		<b>A1RS-2571-C2</b> <b>A1RS-2572-C2</b>	14W IC 18W IC
<b>Remodel Non-IC</b>		<b>A1RS-3571-C2</b> <b>A1RS-3572-C2</b>	14W Non-IC 18W Non-IC

## A1RS-\_\_\_\_-C2

Example: A1RS-2471-C2

### GLARE CONTROL ACCESSORIES

<b>LENS-11-HCM</b>	<i>Honeycomb Louver</i>
<b>LENS-11P-CRL-BK</b>	<i>Cross Louver</i>

### LENS ACCESSORIES

<b>LENS-11</b>	<b>AMB</b> <b>RED</b> <b>BLU</b> <b>GRN</b> <b>SPR</b> <b>BEL</b>	<i>Amber</i> <i>Red</i> <i>Blue</i> <i>Green</i> <i>Spread</i> <i>Beam Elongating</i>
----------------	--	--

aispire.com

Phone (800) 526.2588

Fax (800) 526.2585

**Headquarters**

44 Harbor Park Drive,

Port Washington, NY 11050

**Georgia Distribution Center**

1600 Distribution Ct,

Lithia Springs, GA 30122

**Texas Distribution Center**

1700 S J Elmer Weaver Fwy Suite 100,

Cedar Hill, TX 75104

**California Distribution Center**

1750 S Archibald Ave,

Ontario, CA 91761