

A1RS-W46A

QUARTUS ALPINE 2" - Round Wall Wash Trim



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION


The QUARTUS ALPINE Recessed series offers high performance static white lighting that provide outputs up to 2000 lumens on 2" styles. The series features superlative glare control with 30° shielding, 35° vertical tilting with 360° horizontal rotation, and uniform floor-to-ceiling wall washing. A full line of round and square, trimmed and trimless luminaires deliver versatile lighting solutions for various applications. The recessed series includes easy serviceability of both the light engine and driver.

FEATURES

- Two-piece die-cast construction
- Light engine mounted on trim with springs for easy replacement
- 365° horizontal rotation
- Designed for even wall illumination both vertically and horizontally
- 8 year product warranty

SPECIFICATIONS

- Construction:** Durable die-cast aluminum construction
- Input:** Universal 120-277V AC 50/60 Hz
- Dimming:** Electronic Low Voltage (ELV): 100%-1%
TRIAC: 100%-1% 0-10V: 100-1%
- Light Source:** High output 3-step Mac Adam Ellipse COB
Rated life of 50,000 hours at L70
- Mounting:** Heavy gauge retention clips support trim firmly.
Safety cabling standard. Ceiling cutout: Ø 3 1/2"
Accommodates 1/2" - 1 1/4" ceiling thickness
- Finish:** Electrostatically powder coated White, Black, Dark Bronze. Enamel coated Haze.
- Standards:** ETL & cETL Wet Location Listed, Energy Star 2.0, Title 24 JA8 Compliant.

	Model	Beam	*Lumens	*CBCP	Color Temp	CRI	Finishes	Reflector/Trim
	A1RS-W46A Round Trimless	A Asym	1845	N/A	27 2700K	90	BK DB HZ WT	Black Dark Bronze Haze White
			1940	N/A	30 3000K	90		

A1RS-W46A-__ __

Example: **A1RS-W46A-30WT**

*Lumens shown in the table are reference values for 3000K trim with **3** housing. Use multiplier table below to determine the output for other combinations.

MULTIPLIER		TRIM	
		27	30
HOUSING	3 (25W)	0.95	1.00
	2 (21W)	0.83	0.87
	1 (15W)	0.61	0.64

Example: **A1RS-W46A-30WT** with 1 housing: 1465 lm (Reference Output) x 0.64 (Multiplier) = 935 lm

Please see next page for housing units (required)

aispire.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters
44 Harbor Park Drive,
Port Washington, NY 11050

Georgia Distribution Center
1600 Distribution Ct,
Lithia Springs, GA 30122

Texas Distribution Center
1700 S J Elmer Weaver Fwy Suite 100,
Cedar Hill, TX 75104

California Distribution Center
1750 S Archibald Ave,
Ontario, CA 91761

A1RS-W46A

QUARTUS ALPINE 2" - Round Wall Wash Trim

HOUSING

(Required)

		Model
New Construction IC Airtight		A1RS-2661 A1RS-2662 A1RS-1663 15W IC 21W IC 25W Non-IC
Remodel Non-IC		A1RS-3661 A1RS-3662 A1RS-3663 15W Non-IC 21W Non-IC 25W Non-IC

A1RS-__

Example: A1RS-2661