A1RS-W56A

QUARTUS ALPINE 2" - Square Wall Wash Trim





PRODUCT DESCRIPTI	PRODU	JCT	DESCR	RIPTI	ON
-------------------	--------------	-----	-------	-------	-----------

The QUARTUS ALPINE Recessed series offers high performance static white lighting that provide outputs up to 2000 lumens on 2" styles. The series features superlative glare control with 30° shielding, 35° vertical tilting with 360° horizontal rotation, and uniform floor-to-ceiling wall washing. A full line of round and square, trimmed and trimless luminaires deliver versatile lighting solutions for various applications. The recessed series includes easy serviceability of both the light engine and driver.

FEATURES

- · Two-piece die-cast construction
- · Light engine mounted on trim with springs for easy replacement
- · Designed for even wall illumination both vertically and horizontally
- · 8 year product warranty

Fixture Type:
Catalog Number:
Project:
Location:

SPECIFICATIONS

Construction: Durable die-cast aluminum construction

Input Universal 120-277V AC 50/60 Hz

Dimming: Electronic Low Voltage (ELV): 100%-1% TRIAC: 100%-1% 0-10V: 100-1%

Light Source: High output 3-step Mac Adam Ellipse COB

Rated life of 50,000 hours at L70

Mounting: Heavy gauge retention clips support trim firmly.

Safety cabling standard. Ceiling cutout: Ø 3 1/2" Accommodates 1/2 "- 1 1/4" ceiling thickness

Finish: Electrostatically powder coated White, Black,

Dark Bronze. Enamel coated Haze.

Standards: ETL & cETL Wet Location Listed, Energy Star 2.0,

Title 24 JA8 Compliant.

	Model	Beam	*Lumens	CBCP	Color Temp	CRI	Finishes	Reflector/Trim
4 34"	A1RS-W56A Square Trim	A Asym	1360	N/A	27 2700K	90	DB HZWT	Black Dark Bronze Haze/White White
+ 2¼" + - 4"			1435	N/A	30 3000K	90		

A1RS-W56A-____ Example: A1RS-W56A-30WT

Lumens shown in the table are reference values for 3000K trim with 3 housing. Use multiplier table below to determine the output for other combinations.

MULTIPLIER		TRIM			
		27	30		
HOUSING	3 (25W)	0.95	1.00		
	2 (21W)	0.83	0.87		
	1 (15W)	0.61	0.64		

Example: A1RS-W56A-30WT with 1 housing: 1435 lm (Reference Output) x 0.64 (Multiplier) = 915 lm


Please see next page for housing units (required)

aispire.com	Headquarters	Georgia Distribution Center	Texas Distribution Center	California Distribution Center
Phone (800) 526.2588	44 Harbor Park Drive,	1600 Distribution Ct,	1700 S J Elmer Weaver Fwy Suite 100,	1750 S Archibald Ave,
Fax (800) 526.2585	Port Washington, NY 11050	Lithia Springs, GA 30122	Cedar Hill, TX 75104	Ontario, CA 91761

A1RS-W56A







A1RS-___

Example: A1RS-2661