A1RS-W57A

QUARTUS ALPINE 2" - Square Wall Wash Trimless





PRODUCT DESCRIPTION

The QUARTUS ALPINE Recessed series offers high performance static white lighting that provide outputs up to 2000 lumens on 2" styles. The series features superlative glare control with 30° shielding, 35° vertical tilting with 360° horizontal rotation, and uniform floor-to-ceiling wall washing. A full line of round and square, trimmed and trimless luminaires deliver versatile lighting solutions for various applications. The recessed series includes easy serviceability of both the light engine and driver.

FEATURES

- · Two-piece die-cast construction
- · Light engine mounted on trim with springs for easy replacement
- · Designed for even wall illumination both vertically and horizontally
- · 8 year product warranty

| Fixture Type: |
|-----------------|
| Catalog Number: |
| Project: |
| Location: |

SPECIFICATIONS

Construction: Durable die-cast aluminum construction

Input Universal 120-277V AC 50/60 Hz

Dimming: Electronic Low Voltage (ELV): 100%-1%

TRIAC: 100%-1% 0-10V: 100-1%

Light Source: High output 3-step Mac Adam Ellipse COB

Rated life of 50,000 hours at L70

Mounting: Heavy gauge retention clips support trim firmly.

Safety cabling standard. Ceiling cutout: Ø 3 1/2 " Accommodates 1/2 " - 1 1/4 " ceiling thickness

Finish: Electrostatically powder coated White, Black,

Dark Bronze. Enamel coated Haze.

Standards: ETL & cETL Wet Location Listed, Energy Star 2.0,

Title 24 JA8 Compliant.

| | Model | Beam | *Lumens | CBCP | Color Temp | CRI | Finishes | Reflector/Trim |
|-----------|-------------------------------------|--------|---------|------|------------------------|-----|----------|---------------------------------------|
| 4-34" | A1RS-W57A Square Trimless | A Asym | 1360 | N/A | 27 2700K | 90 | DB HZ | Black Dark Bronze Haze White |
| F 21/4" + | | | 1435 | N/A | 30 <i>3000K</i> | 90 | | |

Lumens shown in the table are reference values for 3000K trim with 3 housing. Use multiplier table below to determine the output for other combinations.

| MULTIPLIER | | TRIM | | | |
|------------|---------|------|------|--|--|
| MOLTIPL | JEK | 27 | 30 | | |
| | 3 (25W) | 0.95 | 1.00 | | |
| HOUSING | 2 (21W) | 0.83 | 0.87 | | |
| | 1 (15W) | 0.61 | 0.64 | | |

Example: A1RS-W57A-30WT with 1 housing: 1435 lm (Reference Output) x 0.64 (Multiplier) = 915 lm

Please see next page for housing units (required)

| aispire.com | Headquarters | Georgia Distribution Center | Texas Distribution Center | California Distribution Center |
|----------------------|---------------------------|-----------------------------|--------------------------------------|--------------------------------|
| Phone (800) 526.2588 | 44 Harbor Park Drive, | 1600 Distribution Ct, | 1700 S J Elmer Weaver Fwy Suite 100, | 1750 S Archibald Ave, |
| Fax (800) 526.2585 | Port Washington, NY 11050 | Lithia Springs, GA 30122 | Cedar Hill, TX 75104 | Ontario, CA 91761 |

A1RS-W57A





| HOUSING (Required) | | Model | Power |
|---------------------------------|---|-------------------------------------|--------------------------------|
| New Construction IC Airtight | 5%" 3½" | | |
| | 10" | A1RS-2571 A1RS-2572 A1RS-1573 | 15W IC 21W IC 25W Non-IC |
| Remodel Non-IC | 5½" — 13½" — 5¾" — 5¾" — 2" — 2" — 2" — 2" — 2" — 2" — 2" — | A1RS-3571 A1RS-3572 A1RS-3573 | 15W IC 21W IC 25W Non-IC |

A1RS-___

Example: A1RS-2571