

A1RT-D46M-C2

QUARTUS ATMOSPHERE 4" - Round Downlight Trim



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION


QUARTUS ATMOSPHERE recessed luminaires merge quality and value with the latest tunable white technology to demonstrate the beauty and power of 90 CRI illumination. The 4" aperture size features a robust lumen output for larger spaces with higher ceilings. The fixtures are also ideal for sunrise/sunset scenes, as well as accenting artwork, furniture and architectural decor while creating personalized and meaningful experiences for your clients.

FEATURES

- Two-piece die-cast construction
- Light engine mounted on trim with springs for easy replacement
- 30° shielding angle design for better visual comfort
- Field changeable beam angle with reflectors provided
- Accepts one Lens or glare control accessory
- 8 year product warranty

SPECIFICATIONS

- Construction:** Durable die-cast aluminum construction
- Input:** Universal 120-277V AC 50/60 Hz
- Dimming:** 2-channel DMX512-A RDM: 100-0.1%
- Light Source:** 3-step Mac Adam Ellipse Tunable White COB
Rated life of 50,000 hours at L70
- Mounting:** Heavy gauge retention clips support trim firmly. Safety cabling standard.
- Finish:** Electrostatically powder coated White, Black, Dark Bronze. Enamel coated Haze.
- Standards:** ETL & cETL Wet Location Listed, Title 24 JA8 Compliant.

	Model	Beam	*Lumens	*CBCP	Color Temp	CRI	Finishes	Reflector/Trim
	A1RT-D46M Round Trim	N 27°	1610	4260	C2 1800K - 4000K	90	BK DB HZWT WT	Black Dark Bronze Haze/White White
		F 42°	1660	2865				
		W 55°	1670	2100				

A1RT-D46M-C2__

Example: **A1RT-D46M-C2WT** (Beam F-42° reflector is pre-installed. Beams N-27° and W-55° reflectors are included.)

* Lumens and CBCP are reference values for 3000K trim with **3** housing. Use multiplier table below to determine the output for other combinations.

LUMENS AND CBPC MULTIPLIER						
Housing Power Level	Color Temperature					
	1800K	2200K	2700K	3000K	3500K	4000K
1 (14W)	0.42	0.48	0.53	0.56	0.59	0.63
2 (19W)	0.59	0.67	0.74	0.78	0.83	0.88
3 (26W)	0.76	0.86	0.95	1.00	1.07	1.13

Please see next page for housing units (required)

aispire.com	Headquarters	Georgia Distribution Center	Texas Distribution Center	California Distribution Center
Phone (800) 526.2588	44 Harbor Park Drive,	1600 Distribution Ct,	1700 S J Elmer Weaver Fwy Suite 100,	1750 S Archibald Ave,
Fax (800) 526.2585	Port Washington, NY 11050	Lithia Springs, GA 30122	Cedar Hill, TX 75104	Ontario, CA 91761

A1RT-D46M-C2

QUARTUS ATMOSPHERE 4" - Round Downlight Trim

HOUSING (Required)		Model	Power
<p>New Construction IC Airtight</p>		<p>A1RT-2661-C2 A1RT-2662-C2 A1RT-2663-C2</p>	<p>14W IC 19W IC 26W IC</p>
<p>Remodel Non-IC</p>		<p>A1RT-3661-C2 A1RT-3662-C2 A1RT-3663-C2</p>	<p>14W Non-IC 19W Non-IC 26W Non-IC</p>

A1RT-____-C2

Example: **A1RT-3661-C2**

GLARE CONTROL ACCESSORIES

<p>LENS-16-HCM LENS-16P-CRL-BK</p>	<p><i>Honeycomb Louver</i> <i>Cross Louver</i></p>
--	--

LENS ACCESSORIES

<p>LENS-16</p>	<p>AMB RED BLU GRN SPR BEL</p>	<p><i>Amber</i> <i>Red</i> <i>Blue</i> <i>Green</i> <i>Spread</i> <i>Beam Elongating</i></p>
-----------------------	--	--