## A1RT-W47A-DW

## QUARTUS ASTRO 4" - Round Wall Wash Trimless





Fixture Type:
Catalog Number:
Project:
Location:

#### PRODUCT DESCRIPTION

QUARTUS ASTRO Recessed luminaires are high performance Dim-to-Warm LED luminaires with outputs up to 1300 lumens on 4" styles. The series features superlative glare control with 30° shielding, 45° vertical tilting with 360° horizontal rotation, and uniform floor-to-ceiling wall washing. Two power level options and a full line of round and square, trimmed and trimless luminaires deliver versatile lighting solutions for various applications. The QUARTUS recessed family offers outstanding value and quality, backed by exceptional serviceability that includes easy replacement of both the light engine and driver.

#### **FEATURES**

- · Two-piece die-cast construction
- · Light engine mounted on trim with springs for easy replacement
- 365° horizontal rotation
- · Designed for even wall illumination both vertically and horizontally
- 8 year product warranty

#### **SPECIFICATIONS**

Construction: Durable die-cast aluminum construction

Input Universal 120-277V AC 50/60 Hz

Dimming: Electronic Low Voltage (ELV): 100%-1% Triac: 100%-1% 0-10V: 100-1%

**Light Source**: High output 3-step Mac Adam Ellipse COB

Rated life of 50,000 hours at L70

**Mounting:** Heavy gauge retention clips support trim firmly.

Safety cabling standard. Ceiling cutout: Ø 4 3/4" Accommodates 1/2 "- 1 1/4" ceiling thickness

Finish: Electrostatically powder coated White, Black,

Dark Bronze. Enamel coated Haze.

Standards: ETL & cETL Wet Location Listed,

Title 24 JA8 Compliant

	Model	Beam	*Lumens	*CBCP	Color Temp	CRI	Finishes	Reflector/ Trim
5 5/8"	A1RT-W47A Round Trimless	A Asym	950	N/A	<b>DW</b> 3000K - 1800K	90	BK DB HZ WT	Black Dark Bronze Haze White

### A1RT-W47A-DW\_\_\_

Example: A1RT-W47A-DWWT

\*Lumens shown in the table is a reference value for DW trim with 19W housing. Use multiplier table below to determine the output for the other combination.

MULTIPLIE	R	TRIM			
HOUSING	19W	1.00			
	13W	0.69			

Example: A1RT-W47A-DWWT with 13W housing: 950 lm (Reference Output) x 0.69 (Multiplier) = 655 lm

Please see next page for housing units (required)

aispire.com Headquarters Georgia Distribution Center Texas Distribution Center California Distribution Center


Phone (800) 526.2588 44 Harbor Park Drive, 1600 Distribution Ct, 1700 S J Elmer Weaver Fwy Suite 100, 1750 S Archibald Ave,

Port Washington, NY 11050 Lithia Springs, GA 30122 Cedar Hill, TX 75104 Ontario, CA 91761

# A1RT-W47A-DW







A1RT-\_\_\_-DW

Example: A1RT-2471-DW