A1RT-W56A

QUARTUS ALPINE 4" - Square Wall Wash Trim





PRODUCT DESCRIPTION

The QUARTUS ALPINE Recessed series offers high performance white lighting that provide outputs up to 2,400 lumens on 4" styles. The series features superlative glare control with 30° shielding, 45° vertical tilting with 360° horizontal rotation, and uniform floor-to-ceiling wall washing. A full line of round and square, trimmed and trimless luminaires deliver versatile lighting solutions for various applications. The recessed series includes easy replacement of both the light engine and driver.

FEATURES

- · Two-piece die-cast construction
- · Light engine mounted on trim with springs for easy replacement
- · Designed for even wall illumination both vertically and horizontally
- · 8 year product warranty

Fixture Type:	
Catalog Numbe	er:
Project:	
Location:	

SPECIFICATIONS

Construction: Durable die-cast aluminum construction **Input**Universal 120-277V AC 50/60 Hz

Dimming: Electronic Low Voltage (ELV): 100%-1%

TRIAC: 100%-1%
0-10V: 100-1%

Light Source: High output 3-step Mac Adam Ellipse COB

Rated life of 50,000 hours at L70

Mounting: Heavy gauge retention clips support trim firmly.

Safety cabling standard. Ceiling cutout: Ø 4 3/4" Accommodates 1/2"- 1 1/4" ceiling thickness

Finish: Electrostatically powder coated White, Black,

Dark Bronze. Enamel coated Haze.

Standards: ETL & cETL Wet Location Listed,

Title 24 JA8 Compliant.

	Model	Beam	*Lumens	*CBCP	Color Temp	CRI	Finishes	Reflector/Trim
5%"	A1RT-W56A Square Trim	A Asym	1770	N/A	27 2700K	90	DB HZWT	Black Dark Bronze Haze/White White
			1865	N/A	30 <i>3000K</i>	90		

A1RT-W56A-___ __ Example: A1RT-W56A-30WT

Lumens shown in the table are reference values for 3000K trim with 4 housing. Use multiplier table below to determine the output for other combinations.


MULTIPLIER		TRIM			
		27	30		
	4 (28W)	0.95	1.00		
HOUSING	3 (25W)	0.84	0.88		
	2 (19W)	0.65	0.68		
	1 (13W)	0.45	0.47		

Example: A1RT-W56A-30WT with 1 housing: 1865 lm (Reference Output) x 0.47 (Multiplier) = 875 lm

Please see next page for housing units (required)

aispire.com	Headquarters	Georgia Distribution Center	Texas Distribution Center	California Distribution Center
Phone (800) 526.2588	44 Harbor Park Drive,	1600 Distribution Ct,	1700 S J Elmer Weaver Fwy Suite 100,	1750 S Archibald Ave,
Fax (800) 526.2585	Port Washington, NY 11050	Lithia Springs, GA 30122	Cedar Hill, TX 75104	Ontario, CA 91761

A1RT-W56A





HOUSING (Required)		Model	Power
New Construction IC Airtight	10" L 45%" -1 24" max	A1RT-2661 A1RT-2662 A1RT-2663 A1RT-1664	13W IC 19W IC 25W IC 28W Non-IC
Remodel Non-IC	1434" 1736" 2½"	A1RT-3661 A1RT-3662 A1RT-3663 A1RT-3664	13W Non-IC 19W Non-IC 25W Non-IC 28W Non-IC

A1RT-___

Example: A1RT-2661